



MEGAFLAT

RUBBER ENDLESS FLAT BELTS

MEGAFLAT belts are truly endless mandrel moulded, available in both polyurethane or chloroprene rubber, with either polyester, aramide or cotton reinforcements.

MEGAFLAT FEATURES:

- High flexibility
- Small pulley diameters
- Dimensional accuracy
- High speed
- Energy efficient
- Low noise and vibration
- Low maintenance
- Good chemical and ozone resistance
- High friction surface

MEGAFLAT belts are particularly suitable for both power transmission and conveying.

RUBBER				
	T 75	T 108	T 110	T 120
TENSILE REINFORCEMENT	POLYESTER FABRIC	POLYESTER/COTTON	POLYESTER	POLYESTER
INSTALLATION TENSION X CM WIDTH (N) ENDLESS	150	260	270	350
MIN. PULLEY DIA. mm	6	10	15	20
THICKNESS mm	0,5	0,65	0,9	1,4
STANDARD LENGTH mm	200/3850	200/3850	200/3850	470/3850
COATING MATERIAL	NEOPRENE	NEOPRENE	NEOPRENE	NEOPRENE
ANTISTATIC	YES	YES	YES	YES

	T 150	T 155	T 200
TENSILE REINFORCEMENT	POLYESTER	POLYESTER / ARAMID	POLYESTER FABRIC
INSTALLATION TENSION X CM WIDTH (N) ENDLESS	300	500	400
MIN. PULLEY DIA. mm	15	30	20
THICKNESS mm	0,9	1,6	1,1
STANDARD LENGTH mm	200/3850	470/3850	200/3850
COATING MATERIAL	NEOPRENE	NEOPRENE	NEOPRENE
ANTISTATIC	YES	YES	YES