



MEGAFLAT

PU ENDLESS FLAT BELTS

POLYURETHANE				
	P 0	P 102		
TENSILE REINFORCEMENT	NO FABRIC	ELASTIC		
INSTALLATION TENSION X CM WIDTH (N) ENDLESS	–	10		
MIN. PULLEY DIA. mm	8	25		
THICKNESS mm	0,9	1,8*		
STANDARD LENGTH mm	210/2500	210/2500		
COATING MATERIAL	NO	POLYURETHANE/SILICONE		
ANTISTATIC	NO	POSSIBLE		
	P 108	P 110	P 120	P 155
TENSILE REINFORCEMENT	POLYESTER / COTTON	POLYESTER FABRIC	POLYESTER FABRIC	ARAMID /POLYESTER
INSTALLATION TENSION X CM WIDTH (N) ENDLESS	200	150	300	350
MIN. PULLEY DIA. mm	8	12	20	30
THICKNESS mm	0,8*	1,0*	1,5*	2*
STANDARD LENGTH mm	210/3850	210/3850	210/4300	210/4300
COATING MATERIAL	POLYURETHANE /SILICONE	POLYURETHANE /SILICONE	POLYURETHANE /SILICONE	POLYURETHANE /SILICONE
ANTISTATIC	POSSIBLE	POSSIBLE	POSSIBLE	POSSIBLE
	S 108	S 110	S 120	S 155
TENSILE REINFORCEMENT	POLYESTER / COTTON	POLYESTER	POLYESTER	ARAMID /POLYESTER
INSTALLATION TENSION X CM WIDTH (N) ENDLESS	180	125	350	400
MIN. PULLEY DIA. mm	8	12	20	25
THICKNESS mm	0,8*	1,0*	1,5*	2,0*
STANDARD LENGTH mm	210/3850	210/3850	210/4300	210/3800
COATING MATERIAL	POLYURETHANE /SILICONE	POLYURETHANE /SILICONE	POLYURETHANE /SILICONE	POLYURETHANE /SILICONE
ANTISTATIC	POSSIBLE	POSSIBLE	POSSIBLE	POSSIBLE

*Increase of thickness by about 0,3/0,5 mm for belts coated both sides.

FLAT BELTS

