

PIX-DUO[®]-XS

Twin-power, Hexagonal Wrap Belts



Features:

- Enhanced product life
- **Transmits power from both the sides**
- **Centre cord provides excellent power transmission and low-stretch**
- Special design provides an excellent flexibility for serpentine drives
- Temperature range: -18°C to +80°C


Sections: AA, BB, CC, 25

Application: Rice mills, husker machines, serpentine drives, poultry feather-pickers, dyeing units, etc.

PIX-Duo®-XS Twin-power, Hexagonal Wrap BeltsSection: AA
Reference Standard: IS 11038-1984**AA / 13x10**

Features :

- Enhanced product life
- Transmits power from both the sides
- Centre cord provides excellent power transmission and low-stretch
- Special design provides an excellent flexibility for serpentine drives
- Temperature range: -18°C to +80°C



Mfg. range	Weight/metre (Kgs)
46" to 254"	0.133


Section	Dimensions (mm)		Angle (Degree)	Reco. min pulley dia.
	Top width	Thickness		
AA	13	10	40	80 mm

• Nominal Length (Inches) : Le

Minimum order quantity:
 Belt length: 46"-254": 58pcs
PIX-Duo®-XS Twin-power, Hexagonal Wrap BeltsSection: BB
Reference Standard: IS 11038-1984**BB / 17x14**

Features :

- Enhanced product life
- Transmits power from both the sides
- Centre cord provides excellent power transmission and low-stretch
- Special design provides an excellent flexibility for serpentine drives
- Temperature range: -18°C to +80°C



Mfg. range	Weight/metre (Kgs)
40" to 924"	0.223


Section	Dimensions (mm)		Angle (Degree)	Reco. min pulley dia.
	Top width	Thickness		
BB	17	14	40	125 mm

• Nominal Length (Inches) : Le

Minimum order quantity:
 Belt length: 40"-924": 40pcs.
PIX-Duo®-XS Twin-power, Hexagonal Wrap BeltsSection: CC
Reference Standard: IS 11038-1984**CC / 22x17**

Features :

- Enhanced product life
- Transmits power from both the sides
- Centre cord provides excellent power transmission and low-stretch
- Special design provides an excellent flexibility for serpentine drives
- Temperature range: -18°C to +80°C



Mfg. range	Weight/metre (Kgs)
73" to 924"	0.385


Section	Dimensions (mm)		Angle (Degree)	Reco. min pulley dia.
	Top width	Thickness		
CC	22	17	40	224 mm

• Nominal Length (Inches) : Le

Minimum order quantity:
 Belt length: 73"-924": 26pcs.
PIX-Duo®-XS Twin-power, Hexagonal Wrap BeltsSection: 25
Reference Standard: IS 11038-1984**25 / 25x22**

Features :

- Enhanced product life
- Transmits power from both the sides
- Centre cord provides excellent power transmission and low-stretch
- Special design provides an excellent flexibility for serpentine drives
- Temperature range: -18°C to +80°C



Mfg. range	Weight/metre (Kgs)
88" to 925"	0.572

Section	Dimensions (mm)		Angle (Degree)	Reco. min pulley dia.
	Top width	Thickness		
25	25	22	40	280 mm

• Nominal Length (Inches) : Le

Minimum order quantity:
 26pcs.